



TF103 & TF103A - BEADLOCK RINGS TO FIT TF RVS BEADLOCK WHEELS: TF100 / TF102 / TF106 / TF107

1. Fit the three locating pins -



2. Use a soapy solution to lubricate the back bead of the tire. Push the tire onto the rim so that half of the bead is pushed into the dropped well of the center of the rim. Apply steady pressure and work your way around the bead until the tire drops onto the wheel. If it is necessary to use tools to help the tire onto the rim, take care not to damage the tire.



3. Centre the bead of the tire over the stepped bead lock edge. On most applications the tire will fit easily over the step. If the tire bead does not drop over the step easily, apply a liberal amount of soap solution to the bead. Mount the beadlock clamping ring onto the three locating pins. Using a cross hatch pattern, tighten all bolts, in steps of 5nm. at a time, working your way around the clamp until 15nm. is achieved.





4. Inflate the tire to the desired air pressure. Do not exceed the tire manufacturers recommended air pressure.

NOTE* DO NOT EXCEED 15nm. ON THE BEADLOCK BOLTS. DO NOT ALLOW THE END OF THE BEADLOCK BOLTS TO DRIVE INTO THE WHEEL. THIS WILL VOID YOUR WARRANTY, AND CAN DAMAGE THE WHEEL.

WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fiftnent or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Lid. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

TF103